



Technische Steekkaart
 Fiche Technique
 Technisches Merkblatt
 Technical Data Sheet

EXC98001/2/3/4

CHARACTERISTIC

EXC98001/2/3/4 is a UV flexo coating with radical curing.

PROPERTIES

Article	Viscosity Din 4 at 21°C	Cure	Hot stampable	Slip	Gloss	Rub/scuff	Property
EXC98001	40-50s	High	No	High	High	High	Formulated without benzophenone
EXC98003	40-50s	High	No	High	High	High	Formulated without benzophenone
EXC98002	40-50s	High	Yes	Medium	High	High	Formulated without benzophenone
EXC98004	40-50s	High	Yes	Medium	High	High	Formulated without benzophenone

TYPES

- Radical chemistry

APPLICATION AREA

- Varnishing machines / coaters

SUITABLE SUBSTRATES (min. surface tension 38 dynes/cm)

- All kinds of paper and board
- Certain corona treated PE-films
- Other substrates: to be tested

REMARKS

- Shelf life: all UV varnishes have a 12-month shelf life guarantee. This guarantee covers 12 months from the date of manufacture (which is mentioned on the label). In order to give this guarantee, certain recommendations must be followed: UV varnishes should be kept on stock at temperatures between 15 - 25°C and they should not be exposed to direct sunlight. If possible, store the varnish in a dark room.
- Stir well before use.

PACKAGING

- 5 kg pail
- 10 kg jerry cans
- 25 kg jerry cans
- 200 kg barrels
- 600 kg containers
- 1000 kg containers

PRODUCT SAFETY

This varnish is NOT suitable for FOOD applications unless a proper risk assessment proves that its use is safe. For further information please contact our local sales team or www.toyoink.eu.